


Surface Mount Super Fast Recovery Rectifier




Features

- Low profile package
- Ideal for automated placement
- Glass passivated chip junction
- High forward surge capability
- Super Fast reverse recovery time
- Meets MSL level 1, per J-STD-020, LF maximum peak of 260 °C

Typical Applications

For use in high frequency rectification of power supplies, inverters, converters, and freewheeling diodes for consumer, and telecommunication.



Mechanical Data

- **Package:** SMAF
Molding compound meets UL 94 V-0 flammability rating, RoHS-compliant, halogen-free
- **Terminals:** Tin plated leads, solderable per J-STD-002 and JESD22-B102
- **Polarity:** Cathode line denotes the cathode end

■ Maximum Ratings ($T_a=25^\circ\text{C}$ Unless otherwise specified)

PARAMETER	SYMBOL	UNIT	E1AF	E1BF	E1CF	E1DF	E1FF	E1GF	E1HF	E1JF	E1KF
Device marking code			E1AF	E1BF	E1CF	E1DF	E1FF	E1GF	E1HF	E1JF	E1KF
Maximum Repetitive Peak Reverse Voltage	V_{RRM}	V	50	100	150	200	300	400	500	600	800
Maximum RMS Voltage	V_{RMS}	V	35	70	105	140	210	280	350	420	560
Maximum DC blocking Voltage	V_{DC}	V	50	100	150	200	300	400	500	600	800
Average rectified output current @60Hz sine wave, resistance load, TL (Fig.1)	I_O	A	1.0								
Forward Surge Current (Non-repetitive) @60Hz Half-sine wave, 1 cycle, $T_j=25^\circ\text{C}$	I_{FSM}	A	30								
Forward Surge Current (Non-repetitive) @1ms, square wave, 1 cycle, $T_j=25^\circ\text{C}$			60								
Current squared time @ $1\text{ms} \leq t \leq 8.3\text{ms}$ $T_j=25^\circ\text{C}$	I^2t	A^2s	3.735								
Storage temperature	T_{stg}	$^\circ\text{C}$	-55 ~ +150								
Junction temperature	T_j	$^\circ\text{C}$	-55 ~ +150								



E1AF THRU E1KF

■ Electrical Characteristics (T_a=25°C Unless otherwise specified)



PARAMETER	SYMBOL	UNIT	TEST CONDITIONS	E1AF	E1BF	E1CF	E1DF	E1FF	E1GF	E1HF	E1JF	E1KF
Maximum instantaneous forward voltage	V _F	V	I _{FM} =1.0A	1.0			1.3			1.7		1.85
Maximum reverse recovery time	t _{rr}	ns	I _F =0.5A, I _R =1.0A, I _{rr} =0.25A	35								
Maximum DC reverse current at rated DC blocking voltage	I _R	μA	T _j =25°C	5.0								
			T _j =125°C	100								
Typical junction capacitance	C _j	pF	Measured at 1MHz and Applied Reverse Voltage of 4.0 V.D.C	18			12		8		10	

■ Thermal Characteristics (T_a=25°C Unless otherwise specified)

PARAMETER	SYMBOL	UNIT	E1AF	E1BF	E1CF	E1DF	E1FF	E1GF	E1HF	E1JF	E1KF
Typical Thermal resistance	R _{θJ-A} ⁽¹⁾	°C/W	60								
	R _{θJ-L} ⁽¹⁾		20								
	R _{θJ-C} ⁽¹⁾		18								

Note:
 (1) Thermal resistance from junction to ambient and from junction to lead mounted on P.C.B. with 0.2" x 0.2" (5.0 mm x 5.0 mm) copper pad areas

■ Characteristics (Typical)





E1AF THRU E1KF






FIG.5: Diagram of circuit and Testing wave form of reverse recovery time




Ordering Information (Example)

PREFERRED P/N	PACKING CODE	UNIT WEIGHT(g)	MINIMUM PACKAGE(pcs)	INNER BOX QUANTITY(pcs)	OUTER CARTON QUANTITY(pcs)	DELIVERY MODE
E1AF-E1KF	F1	Approximate 0.034	3000	24000	96000	7" reel
E1AF-E1KF	F2	Approximate 0.034	10000	/	160000	13" reel
E1AF-E1KF	F3	Approximate 0.034	10000	/	120000	13" reel
E1AF-E1KF	F4	Approximate 0.034	7500	/	120000	13" reel




E1AF THRU E1KF

■ Outline Dimensions



SMAF		
Dim	Min	Max
A	2.40	2.80
B	1.35	1.45
C	3.40	3.60
D	4.40	4.80
E	1.05	1.25
F	0.50	1.00
G	0.15	0.22

■ Suggested pad layout



SMAF	
Dim	Millimeters
P1	6.50
P2	4.00
P3	1.50
Q1	2.50
Q2	1.70



E1AF THRU E1KF

Disclaimer

The information presented in this document is for reference only. Yangzhou Yangjie Electronic Technology Co., Ltd. reserves the right to make changes without notice for the specification of the products displayed herein to improve reliability, function or design or otherwise.

The product listed herein is designed to be used with ordinary electronic equipment or devices, and not designed to be used with equipment or devices which require high level of reliability and the malfunction of which would directly endanger human life (such as medical instruments, transportation equipment, aerospace machinery, nuclear-reactor controllers, fuel controllers and other safety devices), Yangjie or anyone on its behalf, assumes no responsibility or liability for any damages resulting from such improper use of sale.

This publication supersedes & replaces all information previously supplied. For additional information, please visit our website [http:// www.21yangjie.com](http://www.21yangjie.com) , or consult your nearest Yangjie's sales office for further assistance.